

## **Strike Guard™ Lightning Protection Prepreg Product Index**

<b><u>Product No.</u></b>	<b><u>Description</u></b>
SG4528-015CU-101V	250-350°F curable epoxy adhesive prepreg with a light weight non-woven copper conductive mesh for zone 1A or 2A protection with a high degree of electromagnetic shielding. Please see product data bulletin for details.
SG4528-029CU-102V	250-350°F curable epoxy adhesive prepreg with a medium weight non-woven copper conductive mesh for zone 1A or 2A protection with a high degree of electromagnetic shielding. Please see product data bulletin for details.
SG4528-040CU-103V	250-350°F curable epoxy adhesive prepreg with a heavy weight non-woven copper conductive mesh for zone 1A or 2A protection with a high degree of electromagnetic shielding. Please see product data bulletin for details.
SG4528-016AL-104V	250-350°F curable epoxy adhesive prepreg with a light weight non-woven aluminum conductive mesh for zone 1A or 2A protection with a high degree of electromagnetic shielding. Please see product data bulletin for details.
SG4528-028AL-105V	250-350°F curable epoxy adhesive prepreg with a medium weight non-woven copper conductive mesh for zone 1A or 2A protection with a high degree of electromagnetic shielding. Please see product data bulletin for details.